

**SINGLE RJ45 CONNECTOR MODULE WITH INTEGRATED
10/100 BASE-TX MAGNETICS**

- Complies with requirement of IEEE 802.3u standards.
- RJ-45 connector integrated with transformer/impedance resistor/high voltage capacitor.
- Size same as RJ-45 connector to save PCB board space.
- Reduced EMI radiation to improve EMI performance.
- Design for 10/100 BASE transmission over UTP-5 cable.
- Compliance with ROHS requirements.
- Operating temperature range: 0 to +70 .
- Storage temperature range: -25 to +85 .

**Electrical specifications @ 25**

Part Number	Insertion Loss (dB Max)	Return Loss (dB Min)					Cross Talk (dB Min)		
	0.3-100MHz	30MHz	40 MHz	50 MHz	60 MHz	80 MHz	0.3-30 MHz	30-60 MHz	60-100 MHz
KHU1S041F3 LF	-1.15	-16	-14	-13.5	-13	-10	-40	-35 -30	
KHU1S041Q3 LF	-1.15	-16	-14	-13.5	-13	-10	-40	-35 -30	

Continue

Number	Turns Ratio (±5%)		OCL (uH Min) @ 100KHz/0.1V with 8mA DC Bias	C _{WW} (pF Max)	L.L (uH Max)	HI-POT (V _{rms})	CMR (dB Min)		
	TX	RX					1-30MHz	30-60 MHz	60-125 MHz
KHU1S041F3 LF	1CT:1CT	1CT:1CT	350	--	--	1500	-30	-25	-20
KHU1S041Q3 LF	1CT:1CT	1CT:1CT	350	28	0.4	1500	-30	-25	-20


“LAN-MATE”SERIES

**SINGLE RJ45 CONNECTOR MODULE WITH INTEGRATED
10/100 BASE-TX MAGNETICS**

Page 2 of 3

Mechanicals


KHU1SXXXQ3 LF



- | | |
|---------------------|---|
| 1. Plastic Material | : Thermoplastic (UL 94V-0), Black Housing |
| 2. Metal Shield | : Brass, 20u" inches thick Nickel |
| 3. Spring Wire | : Phosphor bronze with selective gold plating |
| 4. Solder Pin | : 0.46x0.3 mm, Phosphor bronze with solder Plated |
| 5. Durability | : 750 Mating cycles Min. |

PCB Layout Mounting Hole (Top View)

KHU1SXXXQ3 LF




**SINGLE RJ45 CONNECTOR MODULE WITH INTEGRATED
10/100 BASE-TX MAGNETICS**


Specification	Packing Manner	Q'ty per Tube	Q'ty/ Inner box	Q'ty/ Carton
HU1SXXXX3 LF	TUBE	30	720	2880

Schematics

KHU1S041F3 LF



KHU1S041Q3 LF



Part Numbering System

Example BHJack Part Number:

K	H	U	1	S	041Q	3	LF
代表非MD 機構	TAB Vertical RJ-45 JACK	100 BASE (802.3U)	Number of parts “1” : single port	Shield type S: standard shield	for different circuit	高度 16mm	RoHS