


**Feature**




- Designed to meet IEEE 802.3u requirement, including 350uH OCL with 8mA bias.
- Comply with RoHS & Halogen Free requirements.
- Operating temperature range: -40 to +85 .
- Storage temperature range: -40 to +125 .



Electrical Specifications @ 25°C								
Part Number	Turns Ratio (±3%)		OCL (uH Min) @ 100KHz/0.1V with 8mA DC Bias	C <sub>ww</sub> (pF Max)	L.L (uH Max)	DCR ( Max)		HI-POT (Vrms)
	1-3:16-14	6-8:11-9				1-3/6-8	16-14/11-9	
TS8121AMHF	1CT:1CT	1CT:1CT	350	28	0.5	1.1	0.9	1500

Continue										
Part Number	Insertion Loss (dB Max)	Return Loss (dB Min)				Cross talk (dB Min)		DCMR (dB Min)		
	0.3-100 MHz	0.3-30MHz	40MHz	50MHz	60-80MHz	0.3-60MHz	60-100MHz	30MHz	60MHz	100MHz
TS8121AMHF	-1.1	-18	-15.5	-13	-12	-45	-35	-40	-35	-30



**Schematic**



**Mechanical**



**SUGGESTED PAD LAYOUT**



Units: mm[Inches] Tolerances: xx.x0±0.25[0.010]  
 0.xx±0.05[0.002]