

1000 BASE -T QUAD PORT MAGNETICS MODULES

P/N: G4P409RNY LF DATA SHEET

Page :1/2

Feature



- Designed for Ethernet 1000 BASE-T, full Quad port applications.
- Supports 16 pairs of category 5 UTP cable.
- Cable interface for isolation and low common mode emissions.
- Compliant with IEEE 802.3at standard for 1000 BASE-T.
- Compliance with ROHS requirements.
- Operating temperature range: 0 to +70 .
- Storage temperature range: -25 to +105 .


Electrical Specifications @ 25°C

Part Number	Turns Ratio (±5%)		OCL (uH Min) @100KHz/0.1V with 8mA DC Bias	Cross talk Attenuation (dB Min)			HI-POT (Vrms)
	TX	RX		30MHz	60MHz	100MHz	
G4P409RNY LF	1CT:1CT	1CT:1CT	350	-40	-35	-30	1500

Continue

Part Number	Insertion Loss (dB Max)	Return Loss (dB Min)@ Load 100Ω					DCMR (dB Min)		
	1-100MHz	1-30MHz	40MHz	50MHz	60-80MHz	100MHz	30MHz	60MHz	100MHz
G4P409RNY LF	-1.0	-18	-14.4	-13.1	-12	-10	-40	-35	-30

Schematic




1000 BASE -T QUAD PORT MAGNETICS MODULES

P/N: G4P409RNY LF DATA SHEET


Page :2/2

Mechanical



Units: mm[Inches] Tolerances XX.X0 : ± 0.25 [0.010]
0.XX : ± 0.05 [0.002]

PCB Layout mounting Hole (Top View)



Units: mm[Inches] Tolerances XX.X0 : ± 0.25 [0.010]
0.XX : ± 0.05 [0.002]