



P/N: TS6121AM LF DATA SHEET

Feature



- Designed to meet IEEE 802.3u requirement, including 350uH OCL with 8mA bias.
- Lead free for external pins.
- Operating temperature range:-40 to +85 .
- Storage temperature range:-40 to +125 .


Electrical Specifications @ 25°C

Part Number	Turns Ratio		PRI OCL (uH Min) @ 100KHz/0.1V with 8mA Bias	Cw/w (pF Max)	L.L (uH Max)	DCR (Max)		HI-POT (Vrms)
	1-3:16-14	6-8:11-9				1-3/6-8	16-14/11-9	
TS6121AM LF	1CT:1CT	1CT:1CT	350	28	0.5	1.1	0.9	1500


Continue

Part Number	Insertion Loss (dB Max)	Return Loss (dB Min)				Cross talk (dB Min)		DCMR (dB Min)		
		0.3-100 MHz	0.3-30MHz	40MHz	50MHz	60-80MHz	0.3-60MHz	60-100MHz	30MHz	60MHz
TS6121AM LF	-1.1	-18	-15.5	-13	-12	-45	-35	-40	-35	-30

Schematic



Mechanical



Units: mm[Inches] Tolerance: xx.x0±0.25[0.010]
0.xx±0.05[0.002]